



Канатный электротельфер Т10 Передвигаемый одной тележкой, полиспаст 2/1

(1) с микроподъемом

(2) с ограничителем груза

(3) с ограничителем груза и с микроподъемом

Тип	Полиспаст 2/1		Размеры, мм																									
	Высота подъема, м	Грузоподъемность, kg	Скорость подъема m/min				L2	L3	L4	L5	L6	L7	H1	H2	H3	B	B1	B2	B3	B4	B5	e	C	D				
			8	12	8/2	12/2																						
T102...	H1	6	500	648	688	287	225	37	45	415	46	148	204	33	90...	465	300	94...	245...	34	18	850	120					
	H2	9		738	778										60	68								130	492 ⁽¹⁾	365 ⁽²⁾	54	305
	H3	12		818	858										80	88								557 ⁽³⁾				
T103...	H1	6	1000	709	749	310	225	48	55	415	70	148	204	33	90...	465	300	94...	245...	40	18	910	120					
	H2	9		814	854										75	82								130	492 ⁽¹⁾	365 ⁽²⁾	54	305
	H3	12		914	954										100	106								557 ⁽³⁾				
T104...	H1	6	2000	816	880	362	280	45	51	536	80	200	272	42	130...	580	380	125...	270...	45	22	1120	175					
	H2	9		926	990										73	79								150	606 ⁽¹⁾	442 ⁽²⁾	105	335
	H3	12		1026	1090										96	104								668 ⁽³⁾				
T105...	H1	6	3200	856	923	377	280	52	59	536	80	200	272	42	130...	580	380	125...	270...	50	22	1200	175					
	H2	9		976	1043										82	89								150	606 ⁽¹⁾	442 ⁽²⁾	105	335
	H3	12		1086	1153										110	116								668 ⁽³⁾				
T106...	H1	6	5000	905	993	395	310	49	66	595	90	232	317	33	130...	675	430	145...	300...	56	26	1380	210					
	H2	9		1010	1098										75	82								150	682 ⁽¹⁾	508 ⁽²⁾	125	365
	H3	12		1115	1203										101	108								760 ⁽³⁾				

Тип	Полиспаст 2/1		Скорость подъема, м/мин			
	Высота подъема, м	Грузопо- дъемность, kg	8	12	8/2	12/2
			Вес, kg			
Т102...	Н1	6	500	129		147
	Н2	9		135		153
	Н3	12		138		156
Т103...	Н1	6	1000	137		160
	Н2	9		142		165
	Н3	12		152		175
Т104...	Н1	6	2000	290		337
	Н2	9		305		352
	Н3	12		315		362
Т105...	Н1	6	3200	325	335	390
	Н2	9		340	350	405
	Н3	12		355	365	420
Т106...	Н1	6	5000	488		583
	Н2	9		508		603
	Н3	12		528		623